

Si-1050-6S Specifications

Injection	Screw diameter	in(mm)	3.26(83)	3.54(90)	3.93(100)	3.93(100)	4.33(110)	4.33(110)	4.72(120)	
	Injection stroke	in	16.53	17.71	17.71	19.68	19.68	19.68	21.65	
	Theoretical injection capacity	in ³	138.64	174.71	215.65	240.10	290.00	290.00	379.52	
	Injection capacity (PS)	oz	76.14	95.93	118.43	131.59	159.22	159.22	208.44	
	Standard	Injection unit	—	L750EU			M750EU		N1100EU	
		Injection rate	in ³ /s	56.14	65.96	81.46	71.88	86.95	86.95	103.49
		Max. injection speed	in/s	6.69			5.90		5.90	
		Max. injection pressure	psi	32060	27850	22630	27130	22050	25670	21470
		Max. injection holding pressure	psi	28430	24220	20020	24220	20020	22480	18860
	High-pressure	Injection unit	—	—			—		—	
		Injection rate	in ³ /s	—			—		—	
		Max. injection speed	in/s	—			—		—	
		Max. injection pressure	psi	—			—		—	
		Max. injection holding pressure	psi	—			—		—	
	High-speed	Injection unit	—	—			—		—	
		Injection rate	in ³ /s	—			—		—	
		Max. injection speed	in/s	—			—		—	
		Max. injection pressure	psi	—			—		—	
		Max. injection holding pressure	psi	—			—		—	
	Ultrahigh-speed	Injection unit	—	—			—		—	
Injection rate		in ³ /s	—			—		—		
Max. injection speed		in/s	—			—		—		
Max. injection pressure		psi	—			—		—		
Max. injection holding pressure		psi	—			—		—		
Recovery rate (PS)	oz/s	3.30	4.40	5.99	5.64	7.40	6.01	7.64		
Screw revolution speed	min ⁻¹	170			160		130			
Heater capacity	kW	38.80	49.40	53.40	53.40	61.40	61.40	72.10		
Nozzle pressing force	U.S ton	4.4			4.4		6.6			
Clamping	Clamping system	—	Double toggle							
	Clamping force	U.S ton	1050							
	Clamping stroke	in	47.24							
	Min. mold height	in	19.68							
	Max. mold height	in	47.24							
	Tie bar clearance (H×V)	in	51.96×51.96							
	Die plate size (H×V)	in	68.89×68.89							
	Ejector force	U.S ton	27.50							
	Ejector stroke	in	11.81							
Others	Mold height motor output	kW	1.5							
	Nozzle touch motor output	kW	3.5(Servo motor)			3.5(Servo motor)		5.5(Servo motor)		
	Machine dimension <L>	in	460			468.38	477.51	487.36	499.25	
	Machine dimensions <W×H>	in	105.94×99.72			105.97×100.15		105.94×99.09		
	Power source	—	Three-phase AC200V/200, 230V±10% 50Hz/60Hz ※2							
	Main breaker capacity 200V Class【400V Class ※1】	A	400【225】			500【250】		600【350】		
	Total electric capacity	kVA	124			130		179		
	Cable size 200V Class 【400V Class ※1】	in ²	0.38【0.15】			0.38【0.15】		0.62【0.31】		
	Machine weight	U.S ton	64.7(Injection Unit 14.3)			66.9(Injection Unit 16.5)		68.0(Injection Unit 17.6)		

NOTES

- The figures are subject to change without any legal obligation on the part of the manufacture.
- The maximum injecting pressure and the maximum holding pressure are attainable maximum set values. These values may be limited by molding conditions and cycle time.
- The injection rate and the maximum injecting speed are calculated values. These values may be limited by set injecting pressures.
- When a screw with wide diameter is used, some resins may not be accepted.
- When the machine is attached with an option, the capacity of the breaker may be changed.
- Figures in [] are optional.
- Three insulated cables with a rated temperature of 140°F are required. The cable size is calculated on the condition that ambient temperature is 86°F and metallic conduit work is made.
- The total electric capacity is calculated based on the maximum performance of the drive unit. The operating conditions of the injection unit may reduce the total electric capacity.

※1 A transformer (option) is necessary on the machine side.

※2 Use the machine with the maximum voltage of 230V in 60Hz.

It is out of the warranty scope if the electric system is damaged due to the power exceeding above-stated voltage at any time.

■ The highlighted specifications are recommended injection units.

