

Customers' Value Up

TOYO'S High Performance Model Pursuing Multi-Functionality, Inheriting The Features Of The Si Series, And Equipped The Latest IoT And Control Technology.

SI-7
series

TOYO
MACHINERY & METAL

USA Version

PLASTAR Si-55-7 Specifications

Injection	Screw diameter	in (mm)	0.62 (16)	0.70 (18)	0.78 (20)	0.78 (20)	0.94 (24)	1.10 (28)	0.78 (20)	0.94 (24)	1.10 (28)	0.94 (24)	1.10 (28)	1.25 (32)
	Injection stroke	in	2.51	2.83	2.83	2.83	3.77	3.77	2.83	3.77	4.40	3.77	4.40	4.40
	Theoretical injection capacity	in³	0.78	1.11	1.38	1.38	2.65	3.60	1.38	2.65	4.20	2.65	4.20	5.49
	Injection capacity (PS)	oz	0.43	0.60	0.77	0.77	1.44	1.97	0.77	1.44	2.31	1.44	2.31	3.01
	Injection unit	—	B55FA			—			D75FA			D150FA		
	Max. injection speed	in/s	13.77			—			11.81			13.77		
	Injection rate	in³/s	4.29	5.44	6.71	—	—	—	5.75	8.28	11.27	9.66	13.15	17.18
	Max. injection pressure	psi	34230	34230	29150	—	—	—	39890	34230	26540	39890	34230	26400
	Max. injection holding pressure	psi	34230	31330	28430	—	—	—	39890	28430	21320	39890	25670	21320
	Injection unit	—	BH150FA			CH300FA			D150HFA			DH300FA		
	Max. injection speed	in/s	27.55			27.55			19.68			19.68		
	Injection rate	in³/s	8.59	10.87	13.42	13.42	19.32	26.30	9.59	13.80	18.79	13.80	18.79	24.54
	Max. injection pressure	psi	36980	36980	34230	36980	34230	26540	34230	31330	22770	39890	34230	26400
	Max. injection holding pressure	psi	36980	31330	28430	34230	28430	21320	31330	28430	20740	39890	25670	21320
	Recovery rate (PS)	oz/s	0.10	0.14	0.17	0.13	0.26	0.40	0.13	0.26	0.40	0.26	0.40	0.58
	Screw revolution speed	min ⁻¹	500			350			350			350		
	Heater capacity	kW	1.98	2.28	2.58	2.58	3.45	5.5	2.58	3.45	5.5	3.45	5.5	5.85
	Nozzle pressing force	U.S ton	1.10			2.20			2.20			2.20		
Clamping	Clamping system	—	Double toggle											
	Clamping force	U.S ton	55											
	Clamping stroke	in	10.62											
	Min. mold height	in	5.90											
	Max. mold height	in	18.50											
	Tie bar clearance (H × V)	in	14.17 x 14.17											
	Die plate size (H × V)	in	19.68 x 19.68											
	Ejector force	U.S ton	2.15											
Ejector stroke	in	2.75												
Others	Machine dimensions (L) 〈 〉 : DH300FA	in	136.70	136.70	136.70	140.08	142.88	146.66	136.70	138.55	142.33	138.55 <140.40>	142.33 <144.18>	146.30 <148.15>
	Machine dimensions (W × H) 〈 〉 : DH300FA	in	40.71 × 65.75			42.01 × 65.75			40.71 × 65.75			40.71 × 65.75 <42.01 × 65.75>		
	Power source	—	3-phase AC200V±10% 50Hz / AC200V±10% 60Hz / AC230V±10% 60Hz											
	Main breaker capacity	A	B55FA: 75 【50】 BH150FA:100 【50】			CH300FA:150 【100】			D75FA: 75 【50】 D150HFA:100 【50】			D150FA:100 【50】 DH300FA:150 【100】		
	Total electric capacity	kVA	B55FA:9 BH150FA:25			CH300FA:45			D75FA:14 D150HFA:24			D150FA:25 DH300FA:45		
	Incoming supply wire size	in²	B55FA:0.034 【0.022】 BH150FA:0.059 【0.022】			CH300FA:0.093 【0.059】			D75FA:0.034 【0.022】 D150HFA:0.059 【0.022】			D150FA:0.059 【0.022】 DH300FA:0.093 【0.059】		
	Protective earthing wire size	in²	B55FA:0.034 【0.022】 BH150FA:0.034 【0.022】			CH300FA:0.059 【0.034】			D75FA:0.034 【0.022】 D150HFA:0.034 【0.022】			D150FA:0.034 【0.022】 DH300FA:0.059 【0.034】		
	Machine weight	U.S ton	2.8			2.9			2.9			2.9		
Noise (L _{pA})	dB	69.3 dB												

Note

- The information in this document is subject to change without any legal obligation on the part of the manufacture.
- Maximum injection and holding pressures are attainable maximum set values.
- Maximum injection and holding pressures may be limited by the molding conditions and the cycle time.
- The injection rate and the maximum injecting speed are calculated values. These values may be limited by set injecting pressures.
- When the machine is attached with an option, the capacity of the breaker may be changed.
- Figures in 【 】 are 400V class (a transformer (Option) is necessary for the machine) values.
- Noise values determined according to the noise test code given in JIS B 6711:2021 (ISO 20430:2020). Values will be changed by the operating condition.
- Incoming supply wire size is calculated on the condition that three insulated wires with a rated temperature of 140°F and ambient temperature is 86°F and metallic conduit work is made.
- Protective earthing wire size is selected based on the incoming supply wire size.
- The total electric capacity is calculated based on the maximum performance of the drive unit. The operating conditions of the injection unit may reduce the total electric capacity.